

SHOWA 892

SHOWA 892

Forged with fluoroelastomer rubber, the SHOWA 892 chemical and acid resistant glove provides superior resistance to highly corrosive acids. The butyl rubber coating is designed for handling aliphatic and aromatic hydrocarbons, such as Benzene, Toulene, and Xylene. Smooth surface grip allows for increased sensitivity and tactility when handling small components.



BENEFITS

- . Acid-resistant
- Hydrocarbon-resistant •
- . Impermeable

FEATURES

- Unlined Viton® .
- . Butyl rubber
- Smooth grip
- . Unsupported

INDUSTRIES



HAZARDS

Chemical

NORMS & CERTIFICATES



TRADES & APPLICATIONS

- Chemical spray and treatment
- Coating preparation
- Laboratory, pharma & analysis
- Painting & spray workshops
- Fracking
- Drilling



SHOWA 892

PACKAGING

- Pair per polybag: 12
- Polybags per case: 1
- Pair per case: 12

THICKNESS

0.30 mm

COATING

• Viton

SIZES

7/S | 8/M | 9/L | 10/XL | 11/XXL

COLOUR

LENGTH

300 mm

Black

MATERIAL

Unsupported

USER INSTRUCTIONS

Gloves provide protection from chemical and mechanical hazards shown. Do not use gloves that show signs of wear. If required, cleanse outer surface of glove with running water. Discard used gloves in compliance with local regulations. Do not wear gloves when there is a risk of entanglement by moving parts of machines.

DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.