



SHOWA 892

Forged with fluoroelastomer rubber, the SHOWA 892 chemical resistant glove provides superior resistance to aliphatic, aromatic and halogenated hydrocarbons, such as Benzene, Toulene, and Xylene, Methylene chloride, etc. The butyl rubber coating is designed against highly corrosive acids, ketones, esters, alcohols.



BENEFITS

- Acid-resistant
- Hydrocarbon-resistant
- Impermeable

FEATURES

- Unlined Viton®
- Butyl rubber
- Smooth grip
- Unsupported

INDUSTRIES



Chemical

HAZARDS



Chemical

NORMS & CERTIFICATES

Cat III

CE

0299

EN 388:2016



1010X



DFL

EN ISO 374-5:2016



VIRUS

TRADES & APPLICATIONS

- Chemical spray and treatment
- Coating preparation
- Laboratory, pharma & analysis
- Painting & spray workshops
- Fracking
- Drilling

GET IN TOUCH





PACKAGING

- Pair per polybag: 12
- Polybags per case: 1
- Pair per case: 12

THICKNESS

0.30 mm

LENGTH

300 mm

COATING

Viton

SIZES

7/S | 8/M | 9/L | 10/XL | 11/XXL

COLOUR

Black

MATERIAL

Unsupported

USER INSTRUCTIONS

Gloves provide protection from chemical and mechanical hazards shown. Do not use gloves that show signs of wear. If required, cleanse outer surface of glove with running water. Discard used gloves in compliance with local regulations. Do not wear gloves when there is a risk of entanglement by moving parts of machines.

DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.