

SHOWA 465

Featuring a removable cotton/acrylic liner and a full PVC coating, the SHOWA 465 thermal insulation glove protects against chemicals even in cold environments. Protecting up to -20°C, this cold protection glove remains flexible in extreme temperatures. Its rough surface provides increased tactility and grip. The outer layer is impermeable for working in greasy or damp environments, and the inner layer is moisture-wicking and machine washable for added hygiene.



BENEFITS

- Flexible
- Soft liner
- Durable
- Chemical-resistant
- Cold Resistant
- Impermeable
- Forearm protection
- Seamless knit

FEATURES

- Rough grip
- Ergonomic
- Removable liner
- Full PVC Coating
- Insulated

INDUSTRIES

HAZARDS



Chemical



Cold

GET IN TOUCH

SHOWA International | WTC - Tower 2 - Strawinskylaan 1077 XX Amsterdam - The Netherlands
showagroup.com | info@showagroup.eu
© SHOWA GROUP 2024 | All rights reserved

NORMS & CERTIFICATES

Cat III



0120

EN 511:2006



121

EN
388:2016+A1:2018



3221X

EN ISO 374-
1:2016/Type C



KL

EN ISO 374-5:2016



PACKAGING

- Pair per polybag: 6
- Polybags per case: 12
- Pair per case: 72

THICKNESS

1.10mm

LENGTH

300mm

SIZES

8/M | 9/L | 10/XL

COLOUR

- Orange

MATERIAL

- Cotton
- Removable insulated acrylic
- Seamless knit

USER INSTRUCTIONS

Gloves provide protection from chemical and mechanical hazards shown. Do not use gloves that show signs of wear. If required, cleanse outer surface of glove with running water. Discard used gloves in compliance with local regulations. Do not wear gloves when there is a risk of entanglement by moving parts of machines.

DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

GET IN TOUCH

SHOWA International | WTC - Tower 2 - Strawinskylaan 1077 XX Amsterdam - The Netherlands
showagroup.com | info@showagroup.eu
© SHOWA GROUP 2024 | All rights reserved