

SHOWA 890

Forged with fluoroelastomer rubber, the SHOWA 892 chemical resistant glove provides superior resistance to aliphatic, aromatic and halogenated hydrocarbons, such as Benzene, Toulene, and Xylene, Methylene chloride, etc. The butyl rubber coating is designed against highly corrosive acids, ketones, esters, alcohols.



BENEFITS

- Acid-resistant
- Hydrocarbon-resistant
- Impermeable
- Forearm protection

FEATURES

- Unlined Viton®
- Butyl rubber
- Smooth grip
- Unsupported

INDUSTRIES



Chemical

HAZARDS



Chemical

NORMS & CERTIFICATES

Cat III



0299

EN
388:2016+A1:2018



1020X

EN ISO 374-
1:2016/Type B



DFL

EN ISO 374-5:2016



VIRUS

TRADES & APPLICATIONS

- Chemical spray and treatment
- Coating preparation
- Painting & spray workshops
- Washing and cleaning
- Fracking
- Pipe Fitters

GET IN TOUCH

SHOWA International | WTC - Tower 2 - Strawinskylaan 1077 XX Amsterdam - The Netherlands
showagroup.com | info@showagroup.eu
© SHOWA GROUP 2024 | All rights reserved

PACKAGING

- Pair per polybag: 1
- Polybags per case: 12
- Pair per case: 12

THICKNESS

0.70 mm

LENGTH

350 mm

COATING

- Viton

SIZES

8/M | 9/L | 10/XL

COLOUR

- Black

MATERIAL

- Unsupported

USER INSTRUCTIONS

Gloves provide protection from chemical and mechanical hazards shown. Do not use gloves that show signs of wear. If required, cleanse outer surface of glove with running water. Discard used gloves in compliance with local regulations. Do not wear gloves when there is a risk of entanglement by moving parts of machines.

DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

GET IN TOUCH

SHOWA International | WTC - Tower 2 - Strawinskylaan 1077 XX Amsterdam - The Netherlands
showagroup.com | info@showagroup.eu
© SHOWA GROUP 2024 | All rights reserved