



SHOWA 878R

The extra-thick SHOWA 878R chemical and acid resistant glove offers superior protection against highly corrosive acids, ketones, and esters. Butyl rubber provides the highest permeation resistance to gases and water vapors of any material used to make gloves. Rough surface grip ensures optimum precision and increased durability.



BENEFITS

- Acid-resistant
- Impermeable
- Water-resistant

INDUSTRIES



Chemical



Manufacturing



Oil And Gas

FEATURES

- Unlined
- Rolled Cuff
- Rough grip
- Unsupported
- Butyl rubber

HAZARDS



Chemical

NORMS & CERTIFICATES



0299

0020X

EN 388:2016+A1:2018

EN ISO 374-1:2016/Type B

EN ISO 374-5:2016

VIRUS

TRADES & APPLICATIONS

- Chemical spray and treatment
- Coating preparation
- Laboratory, pharma & analysis
- Painting & spray workshops
- Fracking
- Drilling

GET IN TOUCH





PACKAGING

Pair per polybag: 1

THICKNESS

28 mil

LENGTH

14 in

COATING

- Butyl
- Chemical resistant
- Water Resistant

LINERS

Unsupported

SIZES

 $7/S \mid 8/M \mid 9/L \mid 10/XL \mid 11/XXL$

COLOUR

Black

MATERIAL

Unsupported

USER INSTRUCTIONS

Gloves provide protection from chemical and mechanical hazards shown. Do not use gloves that show signs of wear. If required, cleanse outer surface of glove with running water. Discard used gloves in compliance with local regulations. Do not wear gloves when there is a risk of entanglement by moving parts of machines.

DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.