

SHOWA 878

The extra-thick SHOWA 878 chemical and acid resistant glove offers superior protection against highly corrosive acids, ketones, and esters. Butyl rubber provides the highest permeation resistance to gases and water vapors of any material used to make gloves. Smooth surface grip provides unmatched tactility and performance.




BENEFITS

- Acid-resistant
- Impermeable
- Water-resistant

FEATURES

- Unlined
- Rolled Cuff
- Smooth grip
- Unsupported
- Butyl rubber

NORMS & CERTIFICATES



INDUSTRIES

HAZARDS

TRADES & APPLICATIONS

- Chemical spray and treatment
- Coating preparation
- Laboratory, pharma & analysis
- Painting & spray workshops

CONTATTACI

SHOWA International | WTC - Tower 2 - Strawinskyalaan 1077 XX Amsterdam - The Netherlands
 showagroup.com | info@showagroup.eu
 © SHOWA GROUP 2025 | All rights reserved

PACKAGING

- Pair per polybag: 1

THICKNESS

0.70 mm

LENGTH

350 mm

COATING

- Butyl

SIZES

8/M | 9/L | 10/XL | 11/XXL

COLOUR

- Black

MATERIAL

- Unsupported

USER INSTRUCTIONS

Gloves provide protection from chemical and mechanical hazards shown. Do not use gloves that show signs of wear. If required, cleanse outer surface of glove with running water. Discard used gloves in compliance with local regulations. Do not wear gloves when there is a risk of entanglement by moving parts of machines.

DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

CONTACT

SHOWA International | WTC - Tower 2 - Strawinskylaan 1077 XX Amsterdam - The Netherlands
showagroup.com | info@showagroup.eu
© SHOWA GROUP 2025 | All rights reserved