

SHOWA 8814

SHOWA 8814

The SHOWA 8814 heat-resistant gloves are designed to withstand temperatures up to 480°F/260°C for 15 seconds. Even after multiple washings, the 8814 maintains its heatprotective qualities. The textured surface of the neoprene coating provides superior tactile dexterity. Easy donning and doffing makes the glove easy to remove in an emergency.



BENEFITS INDUSTRIES . Machine washable Mining Increased dexterity Food • Easy donning and doffing Heat-resistant HAZARDS FEATURES Rough grip Heat Spray Coated Neoprene **NORMS & CERTIFICATES TRADES & APPLICATIONS** Automotive repairs and maintenance Cat II EN 407:2020 Food Contact

- Mechanical and engineering
- Metal Stamping
- Bakeries & delicatessens
- Casting

CONTATTACI

SHOWA Interntional | WTC - Tower 2 - Strawinskylaan 1077 XX Amsterdam - The Netherlands showagroup.com | info@showagroup.eu © SHOWA GROUP 2024 | All rights reserved

CE

i



1242X



X2XXXX



SHOWA 8814

PACKAGING

- Pair per polybag: 12
- Polybags per case: 1
- Pair per case: 12

LENGTH

355mm

COATING

Neoprene

SIZES

7/S | 8/M | 9/L | 10/XL

COLOUR

• Black

MATERIAL

- Cotton
- Cut and sewn
- Polyester

USER INSTRUCTIONS

Gloves provide protection from chemical and mechanical hazards shown. Do not use gloves that show signs of wear. If required, cleanse outer surface of glove with running water. Discard used gloves in compliance with local regulations. Do not wear gloves when there is a risk of entanglement by moving parts of machines.

DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.