

SHOWA 890

Forged with fluoroelastomer over Butyl rubber, the SHOWA 890 chemical and acid resistant glove provides superior hand and forearm protection against highly corrosive acids. The viton coating is designed for handling aliphatic and aromatic hydrocarbons, such as Benzene, Toluene, and Xylene.



BENEFITS

- Acid-resistant
- Hydrocarbon-resistant
- Impermeable
- Forearm protection






FEATURES

- Unlined Viton®
- Butyl rubber
- Smooth grip
- Unsupported

INDUSTRIES

HAZARDS

NORMS & CERTIFICATES

Cat III	EN 388:2016+A1:2018	EN ISO 374-1:2016+A1:2018/Type A	EN ISO 374-5:2016
			
2777	1120X	ABCDFJLMNPST	VIRUS
EN ISO 21420:2020			
			

TRADES & APPLICATIONS

- Chemical spray and treatment
- Coating preparation
- Painting & spray workshops
- Washing and cleaning
- Fracking
- Pipe Fitters

CONTATTACI

SHOWA International | WTC - Tower 2 - Strawinskylaan 1077 XX Amsterdam - The Netherlands
 showagroup.com | info@showagroup.eu
 © SHOWA GROUP 2025 | All rights reserved

PACKAGING

- Pair per polybag: 1
- Polybags per case: 12
- Pair per case: 12

THICKNESS

0.70 mm

LENGTH

350 mm

COATING

- Viton

SIZES

8/M | 9/L | 10/XL

COLOUR

- Black

MATERIAL

- Unsupported

USER INSTRUCTIONS

Gloves provide protection from chemical and mechanical hazards shown. Do not use gloves that show signs of wear. If required, cleanse outer surface of glove with running water. Discard used gloves in compliance with local regulations. Do not wear gloves when there is a risk of entanglement by moving parts of machines.

DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

CONTATTACI

SHOWA International | WTC - Tower 2 - Strawinskylaan 1077 XX Amsterdam - The Netherlands
showagroup.com | info@showagroup.eu
© SHOWA GROUP 2025 | All rights reserved