

# **SHOWA 878R**

# **SHOWA 878R**

The extra-thick SHOWA 878 chemical and acid resistant glove offers superior protection against highly corrosive acids, ketones, and esters. Butyl rubber provides the highest permeation resistance to gases and water vapors of any material used to make gloves. Rough surface grip ensures optimum precision and increased durability.



# BENEFITS

- . Acid-resistant
- Impermeable •
- Water-resistant

### **INDUSTRIES**

HAZARDS

Chemical



## FEATURES

- Unlined
- Rolled Cuff
- Rough grip •
- Unsupported .
- Butyl rubber

# **NORMS & CERTIFICATES**





2110X



ABCIKLMNPST





EN ISO 374-5:2016

# **TRADES & APPLICATIONS**

- Chemical spray and treatment
- Coating preparation
- Laboratory, pharma & analysis .
- Painting & spray workshops
- Fracking
- Drilling

i

2777

EN ISO 21420:2020

# **GET IN TOUCH**

SHOWA International | WTC - Tower 2 - Strawinskylaan 1077 XX Amsterdam - The Netherlands showagroup.com | info@showagroup.eu © SHOWA GROUP 2024 | All rights reserved



# SHOWA 878R

## PACKAGING

Pair per polybag: 1

# THICKNESS

28 mil

### LENGTH

14 in. (350 mm)

## COATING

- Butyl
- Chemical Resistant
- Water Resistant

## LINERS

Unsupported

## SIZES

7/S | 8/M | 9/L | 10/XL | 11/XXL

### COLOUR

Black

#### MATERIAL

Unsupported

### GRIP

Rough

#### **USER INSTRUCTIONS**

Gloves provide protection from chemical and mechanical hazards shown. Do not use gloves that show signs of wear. If required, cleanse outer surface of glove with running water. Discard used gloves in compliance with local regulations. Do not wear gloves when there is a risk of entanglement by moving parts of machines.

#### DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.