



## **SHOWA DURACOIL 577**

**ANSI CUT LEVEL A3** Thanks to engineered DURACoil wrapping technology, this highly cut and abrasion-resistant glove protects the hand from a range of hazardous applications. The nitrile coating is liquid-proof for added protection and comfort, and the foamed nitrile coating provides superior wet and dry grip while remaining breathable and flexible. Ergonomic shaping replicates the hand's shape to reduce hand fatigue and maximize precision.





#### **BENEFITS**

- Cut-resistant
- Abrasion-resistant
- Oil-resistant
- Breathable
- Flexible
- · Increased dexterity
- Robust grip
- Form-fitting
- Machine washable

## **FEATURES**

- HPPE reinforced
- Fully-coated nitrile
- Foam nitrile palm dip
- · Engineered DURACoil liner
- Ergonomic
- Elasticated wrist cuff

## **INDUSTRIES**



Construction



Mechanical



Manufacturing



Engineering



Oil And Gas

## **HAZARDS**



Cut

## **GET IN TOUCH**



# **SHOWA DURACOIL 577**

## **NORMS & CERTIFICATES**

CE

EN 388:2016

4X42C

EN ISO21420:2020

ANSI/ISEA 105-2016 CUT







## **TRADES & APPLICATIONS**

- Mechanical and engineering
- Plumbing
- Canning
- Mounting and dismantling
- Handling heavy equipment

ANSI/ISEA 105-2016 PUNCTURE



Puncture

## **PACKAGING**

- Pair per polybag: 12 Polybags per case: 12
- Pair per case: 72

## COATING

- Foam nitrile
- Nitrile

#### **SIZES**

6/S | 7/M | 8/L | 9/XL | 10/XXL

## COLOUR

- Grey
- Black

## **MATERIAL**

- Engineered yarn
- HPPE
- Polyester

## **USER INSTRUCTIONS**

Gloves provide protection from chemical and mechanical hazards shown. Do not use gloves that show signs of wear. If required, cleanse outer surface of glove with running water. Discard used gloves in compliance with local regulations. Do not wear gloves when there is a risk of entanglement by moving parts of machines.

## **DISCLAIMER**

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

## **GET IN TOUCH**