

## SHOWA 8814

The SHOWA 8814 heat-resistant gloves are designed to withstand temperatures up to 480°F/260°C for 15 seconds. Even after multiple washings, the 8814 maintains its heat-protective qualities. The textured surface of the neoprene coating provides superior tactile dexterity. Easy donning and doffing makes the glove easy to remove in an emergency.



### BENEFITS

- Machine washable
- Increased dexterity
- Easy donning and doffing
- Heat-resistant

### FEATURES

- Rough grip
- Spray Coated Neoprene

### NORMS & CERTIFICATES

Cat II



EN 388:2016



1242X

EN 407:2020



X2XXXX

Food Contact



EN ISO  
21420:2020



### INDUSTRIES



Food Compliant  
Gloves



Mining

### HAZARDS



Heat

### TRADES & APPLICATIONS

- Automotive repairs and maintenance
- Mechanical and engineering
- Metal Stamping
- Bakeries & delicatessens
- Casting

### GET IN TOUCH

SHOWA International | WTC - Tower 2 - Strawinskylaan 1077 XX Amsterdam - The Netherlands

showagroup.com | info@showagroup.eu

© SHOWA GROUP 2024 | All rights reserved

## PACKAGING

- Pair per polybag: 12
- Polybags per case: 1
- Pair per case: 12

## COATING

- Neoprene

## SIZES

7/S | 8/M | 9/L | 10/XL

## COLOUR

- Black

## MATERIAL

- Cotton
- Cut and sewn
- Polyester

## USER INSTRUCTIONS

Gloves provide protection from chemical and mechanical hazards shown. Do not use gloves that show signs of wear. If required, cleanse outer surface of glove with running water. Discard used gloves in compliance with local regulations. Do not wear gloves when there is a risk of entanglement by moving parts of machines.

## DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

## GET IN TOUCH

SHOWA International | WTC - Tower 2 - Strawinskylaan 1077 XX Amsterdam - The Netherlands  
showagroup.com | info@showagroup.eu  
© SHOWA GROUP 2024 | All rights reserved