

SHOWA 341

The natural rubber coating on the palm is water-resistant to ensure these hard-wearing gloves are highly tactile, even in wet environments. Rough surface grip enables optimum dexterity when working with small components or heavy components. An elasticated wrist cuff prevents dirt and debris from entering the glove, and a seamless knit offers ultimate comfort during long periods of wear.



BENEFITS

- Extra Grip
- Seamless knit
- Increased dexterity
- Breathable
- Flexible
- Form-fitting
- Skin-friendly

FEATURES

- Rough grip
- Ergonomic
- Elasticated wrist cuff
- Latex palm Dipped Coating

INDUSTRIES



Construction



Warehousing & Distribution

HAZARDS



General Purpose

NORMS & CERTIFICATES

Cat II



EN 388:2016



2121X

TRADES & APPLICATIONS

- Decoration
- Drainage, piping
- Flashings and seals
- Guttering and drain pipe
- Install electrical wiring
- Insulation
- Roofing application membranes

GET IN TOUCH

SHOWA International | 579 Edison Street, Menlo, GA 30731, USA | showagroup.com |

USA@SHOWAGroup.com

© SHOWA GROUP 2024 | All rights reserved

PACKAGING

- Pair per polybag: 12
- Polybags per case: 12
- Pair per case: 144

COATING

- Latex

SIZES

6/S | 7/M | 8/L | 9/XL

COLOUR

- Grey

MATERIAL

- Nylon
- Polyester
- Seamless knit

USER INSTRUCTIONS

Gloves provide protection from chemical and mechanical hazards shown. Do not use gloves that show signs of wear. If required, cleanse outer surface of glove with running water. Discard used gloves in compliance with local regulations. Do not wear gloves when there is a risk of entanglement by moving parts of machines.

DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

GET IN TOUCH

SHOWA International | 579 Edison Street, Menlo, GA 30731, USA | [showagroup.com](mailto:USA@SHOWAGroup.com) | USA@SHOWAGroup.com
© SHOWA GROUP 2024 | All rights reserved