

SHOWA 878

The extra-thick SHOWA 878 chemical and acid resistant glove offers superior protection against highly corrosive acids, ketones, and esters. Butyl rubber provides the highest permeation resistance to gases and water vapors of any material used to make gloves. Smooth surface grip provides unmatched tactility and performance.



BENEFITS

- Acid-resistant
- Impermeable
- Water-resistant

FEATURES

- Unlined
- Rolled Cuff
- Smooth grip
- Unsupported
- Butyl rubber

NORMS & CERTIFICATES

Cat III



0299

EN 388:2016



2020X

EN ISO 374-1:2016/Type B



BIK

EN ISO 374-5:2016



INDUSTRIES



Chemical



Mining

HAZARDS



Chemical

TRADES & APPLICATIONS

- Chemical spray and treatment
- Coating preparation
- Laboratory, pharma & analysis
- Painting & spray workshops

GET IN TOUCH

SHOWA International | 579 Edison Street, Menlo, GA 30731, USA | showagroup.com |

USA@SHOWAgroup.com

© SHOWA GROUP 2024 | All rights reserved

PACKAGING

- Pair per polybag: 1

THICKNESS

28 mil

LENGTH

14 in

COATING

- Butyl

SIZES

8/M | 9/L | 10/XL | 11/XXL

COLOUR

- Black

MATERIAL

- Unsupported

USER INSTRUCTIONS

Gloves provide protection from chemical and mechanical hazards shown. Do not use gloves that show signs of wear. If required, cleanse outer surface of glove with running water. Discard used gloves in compliance with local regulations. Do not wear gloves when there is a risk of entanglement by moving parts of machines.

DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

GET IN TOUCH

SHOWA International | 579 Edison Street, Menlo, GA 30731, USA | [showagroup.com | USA@SHOWAgroup.com](mailto:USA@SHOWAgroup.com)
© SHOWA GROUP 2024 | All rights reserved