

SHOWA 890

Forged with fluoroelastomer rubber, the extra-thick SHOWA 890 chemical and acid resistant glove provides superior resistance to highly corrosive acids. The butyl rubber coating is designed for handling aliphatic and aromatic hydrocarbons, such as Benzene, Toulene, and Xylene. Smooth surface grip allows for increased sensitivity and tactility when handling small components.



BENEFITS

- Acid-resistant
- Hydrocarbon-resistant
- Impermeable
- Forearm protection

FEATURES

- Unlined Viton®
- Butyl rubber
- Smooth grip
- Unsupported

NORMS & CERTIFICATES

Cat III



0299

EN 388:2016



1020X

EN ISO 374-1:2016/Type B



DFL

EN ISO 374-5:2016



VIRUS

INDUSTRIES



Chemical

HAZARDS



Chemical

TRADES & APPLICATIONS

- Chemical spray and treatment
- Coating preparation
- Painting & spray workshops
- Washing and cleaning
- Fracking
- Pipe Fitters

GET IN TOUCH

SHOWA International | 579 Edison Street, Menlo, GA 30731, USA | showagroup.com |

USA@SHOWAGroup.com

© SHOWA GROUP 2024 | All rights reserved

PACKAGING

- Pair per polybag: 1
- Polybags per case: 12
- Pair per case: 12

LENGTH

14 in

COATING

- Viton

SIZES

8/M | 9/L | 10/XL

COLOUR

- Black

MATERIAL

- Unsupported

USER INSTRUCTIONS

Gloves provide protection from chemical and mechanical hazards shown. Do not use gloves that show signs of wear. If required, cleanse outer surface of glove with running water. Discard used gloves in compliance with local regulations. Do not wear gloves when there is a risk of entanglement by moving parts of machines.

DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

GET IN TOUCH

SHOWA International | 579 Edison Street, Menlo, GA 30731, USA | [showagroup.com | USA@SHOWAgroup.com](mailto:USA@SHOWAgroup.com)
© SHOWA GROUP 2024 | All rights reserved