SHOWA DURACOIL 386

ANSI CUT LEVEL A3 Don't compromise on flexibility when seeking highly durable cut-resistant gloves. The DURACoil 386 utilizes our advanced HPPE reinforced lining to provide cut and abrasion resistance, without sacrificing dexterity. The microporous coating disperses oil to increase grip. So even for tasks on a smaller scale, such as component assembly, the 386 enables a full range of movement and control.

BENEFITS

- Cut-resistant
- Form-fitting
- Reusable
- Machine washable
- Oil-resistant
- Extra Grip
- Flexible
- Increased dexterity
- Breathable
- Abrasion-resistant
- Seamless knit

FEATURES

- Engineered DURACoil liner
- Ergonomic
- Embossed microporous nitrile coating
- Optimal liner design
- HPPE reinforced

INDUSTRIES

- Aerospace
- Automotive
- Engineering
- Manufacturing
- Mechanical

HAZARDS

- Cut

NORMS & CERTIFICATES

Cat II	EN 388:2016		ANSI/ISEA 105-2016 CUT
CE	4X42C		A3 Cut

TRADES & APPLICATIONS

- Intricate parts handling
- Brick laying
- Flashings and seals
- Maintenance
- Steel fixing
- Component Assembly

GET IN TOUCH
SHOWA International | 579 Edison Street, Menlo, GA 30731, USA | showagroup.com | USA@SHOWAgroup.com

PACKAGING

- Pair per polybag: 6
- Polybags per case: 12
- Pair per case: 72

COATING

- Microporous nitrile

SIZES

6/S | 7/M | 8/L | 9/XL | 10/XXL

COLOUR

- Grey

MATERIAL

- Engineered yarn
- HPPE
- Polyester

TECHNOLOGY

- Duracoil

USER INSTRUCTIONS

Gloves provide protection from chemical and mechanical hazards shown. Do not use gloves that show signs of wear. If required, cleanse outer surface of glove with running water. Discard used gloves in compliance with local regulations. Do not wear gloves when there is a risk of entanglement by moving parts of machines.

DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.