

SHOWA DURACOIL 576

SHOWA DURACOIL 576

ANSI CUT LEVEL A3 Thanks to engineered DURACoil wrapping technology, this highly cut and abrasion-resistant glove protects the hand from a range of hazardous applications. A foamed nitrile coating provides superior wet and dry grip while remaining breathable and flexible. The ergonomic design replicates the hand's shape to reduce hand fatigue and maximize precision.



Construction

Manufacturing

BENEFITS

- . Cut-resistant
- Abrasion-resistant •
- Oil-resistant .
- Breathable •
- . Flexible
- Increased dexterity
- . Robust grip
- Form-fitting
- Machine washable

FEATURES

- HPPE reinforced •
- 3/4 nitrile coating
- Foam nitrile palm dip .
- Engineered DURACoil liner

NORMS & CERTIFICATES

- Ergonomic .
- Elasticated wrist cuff

HAZARDS



Cat II EN 388:2016 ANSI/ISEA 105-2016 CUT CE i

4X42C

TRADES & APPLICATIONS

- Light assembly of oil-coated pieces .
- Mechanical and engineering
- Handling glass and windows
 - Canning
 - Mounting and dismantling

GET IN TOUCH

SHOWA International | 579 Edison Street, Menlo, GA 30731, USA | showagroup.com | USA@SHOWAgroup.com © SHOWA GROUP 2024 | All rights reserved

Cut

INDUSTRIES

Aerospace

Engineering

Mechanical



SHOWA DURACOIL 576

PACKAGING

- Pair per polybag: 12
- Polybags per case: 6
- Pair per case: 72

COATING

- Foam nitrile
- Nitrile

SIZES

6/S | 7/M | 8/L | 9/XL | 10/XXL

COLOUR

- Grey
- Black

USER INSTRUCTIONS

Gloves provide protection from chemical and mechanical hazards shown. Do not use gloves that show signs of wear. If required, cleanse outer surface of glove with running water. Discard used gloves in compliance with local regulations. Do not wear gloves when there is a risk of entanglement by moving parts of machines.

MATERIAL

- Engineered yarn
- HPPE
- Polyester

DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.